



		ELEVATOR MODEL			
		BE15	BE25	BE50	BE100
<b>A</b>	[mm]	287	398	429	573
<b>B</b>	[mm]	670	805	874	1122
<b>C</b>	[mm]	415	525	548	656
<b>D</b>	[mm]	1056	1078	1103	1260
<b>E</b>	[mm]	1025	1300	1400	1800
<b>F</b>	[mm]	1353	1650	1772	2153
<b>G</b>	[mm]	533	741	801	1084
<b>I</b>	[mm]	120	195	195	195
<b>H</b>	[mm]	950	1250	1250	1550
<b>H1</b>	[mm]	1000	1300	1300	1600
<b>M</b>	[mm]	528	737	797	1080
<b>N</b>	[mm]	254	300	300	300
<b>O</b>	[mm]	370	537	562	590
<b>O1</b>	[mm]	23	23	23	23
<b>P</b>	[mm]	493	678	750	760
<b>Q</b>	[mm]	205	280	320	447
<b>R</b>	[mm]	170	170	170	170
<b>S</b>	[mm]	-	-	-	100
<b>T</b>	[mm]	600	680	680	740
<b>T1</b>	[mm]	650	650	840	840
<b>Z</b>	[mm]	160	200	235	280
<b>X</b>	[mm]	160	220	260	380
<b>W</b>	[mm]	744	1033	1090	1416

DUCTS LENGHT 2,95m;2,75m;2,5m;2,25;1.95m;1,75m